LCD Module Specification	First Edition	Approved by	Production Div.
	March 5, 1997	Checked by	Quality Assurance Div.
	Final Revision	Checked by	Design Engineering Div.
	*******	Prepared by	Production Div.
Type No.	DMF 5 0 0 5 N − EW		

Table of Contents

1. General Specifications 2
2. Electrical Specifications 3
3. Optical Specifications 7
4. I/O Terminal 9
5. Test 11
6. Appearance Standards 12
7. Code System of Production Lot 15
8. Type Number 15
9. Applying Precautions 15
10. Handling Precautions 16

Revision History

Rev.	Date	Page	Comment

1. General Specifications

Operating Temp.	:	min. 0℃ ～ max. 50℃
Storage Temp.	:	min. -20℃ ～ max. 60℃
Dot Pixels	:	240 (W) × 64 (H) dots
Dot Size	:	0.49 (W) × 0.49 (H) mm
Dot Pitch	:	0.53 (W) × 0.53 (H) mm
Viewing Area	:	132.0 (W) × 39.0 (H) mm
Outline Dimensions	:	180.0 (W) × 65.0 (H) ×12.0 max. (D) mm
Weight	:	170g max.
LCD Type	:	NSD-7446 (STN / Neutral-mode / Transflective)
Viewing Angle	:	6:00
Control LSI	:	T6963C-0101 (Produced by TOSHIBA)
Data Transfer	:	8-bit parallel data transfer
Backlight	:	Electro Luminescence (EL) / White
Drawings	:	Dimensional Outline UE-31806B

2. Electrical Specifications

2.1. Absolute Maximum Ratings

V_{SS}=0V

Parameter	Symbol	Conditions	Min.	Max.	Units
Supply Voltage (Logic)	V_{CC}-V_{SS}	—	-0.3	7.0	V
Supply Voltage (LCD Drive)	V_{CC}-V_{EE}	—	0	28.0	V
Input Voltage	V_I	—	-0.3	V_{CC}+0.3	V

2.2. DC Characteristics


Ta=25℃, V_{SS}=0V

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Supply Voltage (Logic)	V_{CC}-V_{SS}	—	4.5	—	5.5	V
Supply Voltage (LCD Drive)	V_{CC}-V_{EE}	Shown in 3.1				V
High Level Input Voltage	V_{IH}	V_{CC}=5.0V±10%	V_{CC}-2.2	—	V_{CC}	V
Low Level Input Voltage	V_{IL}	V_{CC}=5.0V±10%	0	—	0.8	V
High Level Output Voltage	V_{OH}	I_{OH}=-0.75mA	V_{CC}-0.3	—	V_{CC}	V
Low Level Output Voltage	V_{OL}	I_{OL}=0.75mA	0	—	0.3	V
Supply Current	I_{CC}	V_{CC}-V_{SS}=5.0V	—	7.0	20.0	mA
	I_{EE}	V_{CC}-V_{EE}=13.0V	—	1.0	10.0	mA

2.3.AC Characteristics


V_{CC}=5.0V±10%

Parameter	Symbol	Min.	Max.	Units
C/$\overline{D}$ Setup Time	t_{CDS}	100	–	ns
C/$\overline{D}$ Hold Time	t_{CDH}	10	–	ns
$\overline{CE}$, $\overline{RD}$, $\overline{WR}$ Pulse Width	t_{CE}, t_{RD}, t_{WR}	80	–	ns
Data Setup Time	t_{DS}	80	–	ns
Data Hold Time	t_{DH}	40	–	ns
Access Time	t_{ACC}	–	150	ns
Output Hold Time	t_{OH}	10	50	ns




2.4.Power Supply ON/OFF Sequence


2.4.1.ON Sequence



2.4.2.OFF Sequence



2.4.3.Reset Sequence



Please maintain the above sequence when turning on and off the power supply of the module.
If V_{EE} is supplied to the module while internal alternate signal for LCD driving (M) is unstable or $\overline{\text{RESET}}$ is active, DC component will be supplied to the LCD panel. This may cause damage to the LCD module.

2.5.Lighting Specifications

2.5.1.Absolute Maximum Rating

Ta=25℃

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage	—	—	—	150	Vrms
Input Frequency	AC 100Vrms	—	—	800	Hz

2.5.2.Operating Characteristics

Ta=25℃

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage	—	—	100	—	Vrms
Input Frequency	—	—	400	—	Hz
Current	AC 100Vrms, 400Hz	—	6.8	8.8	mA
Luminance of Backlight Surface	AC 100Vrms, 400Hz	34	43	—	cd/m²
Life	AC 100Vrms, 400Hz Ta=20℃, 60%RH	—	2000	—	hrs

3. Optical Specifications

3.1.LCD Driving Voltage

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Recommended	V_{CC}-V_{EE}	Ta= 0℃	—	—	15.3	V
LCD Driving Voltage		Ta=25℃	12.1	13.0	13.9	V
Note 1		Ta=50℃	10.9	—	—	V

Note 1 : Voltage (Applied actual waveform to LCD Module) for the best contrast. The range of minimum and maximum shows tolerance of the operating voltage. The specified contrast ratio and response time are not guaranteed over the entire range.

3.2.Optical Characteristics

Ta=25℃, 1/64 Duty, 1/9 Bias, V_D=13.0V (Note 4), $\theta = 0^\circ$, $\phi = -^\circ$

Parameter		Symbol	Conditions	Min.	Typ.	Max.	Units
Contrast Ratio Note 1		CR	$\theta = 0^\circ$, $\phi = -^\circ$	—	7	—	
Viewing Angle			Shown in 3.3				
Response	Rise Note 2	τr	—	—	160	240	ms
Time	Decay Note 3	τd	—	—	160	240	ms

Note 1 : Contrast ratio is defined as follows.

$CR = L_{OFF} / L_{ON}$

L_{ON} : Luminance of the ON segments

L_{OFF} : Luminance of the OFF segments

Note 2 : The time that the luminance level reaches 90% of the saturation level from 0% when ON signal is applied.

Note 3 : The time that the luminance level reaches 10% of the saturation level from 100% when OFF signal is applied.


Note 4 : Definition of Driving Voltage V_D

Assuming that the typical driving waveforms shown below are applied to the LCD Panel at 1/A Duty - 1/B Bias (A : Duty Number, B : Bias Number). Driving voltage V_D is defined as follows.

$V_D = (Vth1+Vth2) / 2$

Vth1 : The voltage V_{O-P} that should provide 50% of the satulation level in the luminance at the segment which the ON signal is applied to.


Vth2 : The voltage V_{O-P} that should provide 50% of the satulation level in the luminance at the segment which the OFF signal is applied to.



3.3.Definition of Viewing Angle and Optimum Viewing Area


・Point ● shows the point where contrast ratio is measured. : $\theta = 0^\circ$, $\phi = -^\circ$

・Driving condition : 1/64 Duty, 1/9 Bias, V_D=13.0V, f_F=70Hz



・Area ▭ shows typ. CR≧2

3.4.System Block Diagram




4.I/O Terminal

4.1.Pin Assignment

No.	Symbol	Level	Function
1	FG	—	Frame Ground
2	V_{SS}	—	Power Supply (0V, GND)
3	V_{CC}	—	Power Supply for Logic
4	V_{EE}	—	Power Supply for LCD Drive
5	$\overline{WR}$	H / L	Write Signal L : Active
6	$\overline{RD}$	H / L	Read Signal L : Active
7	$\overline{CE}$	H / L	Chip Enable Signal L : Active
8	C/$\overline{D}$	H / L	Write Mode H : Command Write L : Data Write Read Mode H : Status Read L : Data Read
9	NC	—	Non-connection
10	$\overline{RESET}$	H / L	Reset Signal L : Reset
11	D0	H / L	Display Data
12	D1	H / L	Display Data
13	D2	H / L	Display Data
14	D3	H / L	Display Data
15	D4	H / L	Display Data
16	D5	H / L	Display Data
17	D6	H / L	Display Data
18	D7	H / L	Display Data
19	FS	H / L	Font Switch H : 6×8 dots L : 8×8 dots
20	NC	—	Non-connection
21	EL	—	Power Supply for EL
22	EL	—	Power Supply for EL


4.2.Example of Power Supply


It is recommended to apply a potentiometer for the contrast adjust due to the tolerance of the driving voltage and its temperature dependence.




R1+R2+VR=10～20K Ω
Tr=2SA1202 or equivalent

4.3.Block Diagram








5. Test

No change on display and in operation under the following test condition.

No.	Parameter	Conditions	Notes
1	High Temperature Operating	50℃±2℃, 96hrs (operation state)	
2	Low Temperature Operating	0℃±2℃, 96hrs (operation state)	3
3	High Temperature Storage	60℃±2℃, 96hrs	4
4	Low Temperature Storage	-20℃±2℃, 96hrs	3, 4
5	Damp Proof Test	40℃±2℃, 90～95%RH, 96hrs	3, 4
6	Vibration Test	Total fixed amplitude : 1.5mm Vibration Frequency : 10～55Hz One cycle 60 seconds to 3 directions of X, Y, Z for each 15 minutes	5
7	Shock Test	To be measured after dropping from 60cm high on the concrete surface in packing state. 	

Note 1 : Unless otherwise specified, tests will be conducted under the following condition.
Temperature : 20±5℃
Humidity : 65±5%

Note 2 : Unless otherwise specified, tests will be not conducted under functioning state.

Note 3 : No dew condensation to be observed.


Note 4 : The function test shall be conducted after 4 hours storage at the normal temperature and humidity after removed from the test chamber.

Note 5 : Vibration test will be conducted to the product itself without putting it in a container.


6. Appearance Standards

6.1. Inspection conditions

The LCD shall be inspected under 40W white fluorescent light.
The distance between the eyes and the sample shall be more than 30cm.
All directions for inspecting the sample should be within 45° against perpendicular line.



6.2. Definition of applicable Zones



A Zone : Active display area
B Zone : Area from outside of "A Zone" to validity viewing area
C Zone : Rest parts





A Zone + B Zone = Validity viewing area

6.3.Standards

<table>
<tr><th>No.</th><th>Parameter</th><th>Criteria</th></tr>
<tr><td>1</td><td>Black and White Spots, Foreign Substances</td><td>(1) Round Shape
<table>
<tr><th rowspan="2">Dimension (mm) \ Zone</th><th colspan="3">Acceptable Number</th></tr>
<tr><th>A</th><th>B</th><th>C</th></tr>
<tr><td>D ≦0.1</td><td>*</td><td>*</td><td>*</td></tr>
<tr><td>0.1 ＜ D ≦0.2</td><td>3</td><td>5</td><td>*</td></tr>
<tr><td>0.2 ＜ D ≦0.25</td><td>2</td><td>3</td><td>*</td></tr>
<tr><td>0.25＜ D ≦0.3</td><td>0</td><td>1</td><td>*</td></tr>
<tr><td>0.3 ＜ D</td><td>0</td><td>0</td><td>*</td></tr>
</table>
D = (Long + Short) / 2 * : Disregard


(2) Line Shape
<table>
<tr><th rowspan="2">X (mm) \ Y (mm) \ Zone</th><th colspan="3">Acceptable Number</th></tr>
<tr><th>A</th><th>B</th><th>C</th></tr>
<tr><td>—</td><td>0.03≧W</td><td>*</td><td>*</td><td>*</td></tr>
<tr><td>2.0≧L</td><td>0.05≧W</td><td>3</td><td>3</td><td>*</td></tr>
<tr><td>1.0≧L</td><td>0.1 ≧W</td><td>3</td><td>3</td><td>*</td></tr>
<tr><td>—</td><td>0.1 ＜W</td><td colspan="3">In the same way (1)</td></tr>
</table>
X : Length Y : Width * : Disregard

Total defects shall not exceed 5.</td></tr>
<tr><td>2</td><td>Air Bubbles (between glass & polarizer)</td><td>
<table>
<tr><th rowspan="2">Dimension (mm) \ Zone</th><th colspan="3">Acceptable Number</th></tr>
<tr><th>A</th><th>B</th><th>C</th></tr>
<tr><td>D ≦ 0.3</td><td>*</td><td>*</td><td>*</td></tr>
<tr><td>0.3 ＜ D ≦ 0.4</td><td>3</td><td>*</td><td>*</td></tr>
<tr><td>0.4 ＜ D ≦ 0.6</td><td>2</td><td>3</td><td>*</td></tr>
<tr><td>0.6 ＜ D</td><td>0</td><td>0</td><td>*</td></tr>
</table>
* : Disregard
Total defects shall not exceed 3.</td></tr>
</table>

No.	Parameter	Criteria
3	The Shape of Dot	(1) Dot Shape (with Dent)  As per the sketch of left hand. (2) Dot Shape (with Projection)  Should not be connected to next dot. (3) Pin Hole  (X+Y) / 2≦0.2mm (Less than 0.1mm is no counted.) (4) Deformation  (X+Y) / 2≦0.2mm Total acceptable number : 1/dot, 5/cell (Defect number of (4) : 1pc.)
4	Polarizer Scratches	Refer to the sample.
5	Polarizer Dirts	If the stains are removed easily from LCDP surface, the module is not defective.
6	Complex Foreign Substance Defects	Black spots, line shaped foreign substances or air bubbles between glass & polarizer should be 5pcs maximum in total.
7	Distance between Different Foreign Substance Defects	D≦0.2 : 20mm or more 0.2＜D : 40mm or more


7. Code System of Production Lot

The production lot of module is specified as follows :



8. Type Number

The type number of module is specified on the back of module as follows :



9. Applying Precautions

Please contact us when questions and/or new problems not specified in this specifications arise.

10. Handling Precautions

Operex Products are designed for use in ordinary electronic devices such as business machines, telecommunications equipment, measurement devices and etc..
Optrex Products are not designed, intended, or authorized for use in any application in which the failure of the product could result in a situation where personal injury or death may occur. These applications include, but are not limited to, life-sustaining equipment, nuclear control devices, aerospace equipment, devices related to hazardous or flammable materials, etc. (If Buyer intends to purchase or use the Optrex Products for such unintended or unauthorized applications, Buyer must secure prior written consent to such use by a responsible officer of Optrex Corporation.) Should Buyer purchase or use Optrex Products for any such unintended or unauthorized application (without such consent), Buyer shall indemnify and hold Optrex and its officers, employees, subsidiaries, affiliates and distributors harmless against all claims, costs, damages and expenses, and reasonable attorney's fees, arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Optrex was negligent regarding the design or manufacture of the part.

1) LCD may be broken because it is made of glass.

2) Polarizer is a soft material and can easily be scratched.

3) Please avoid static electricity.

   ① Please be sure to ground human body and electric appliances during work.
   ② It is preferable to use conductive mat on table and wear cotton clothes or conduction processed fiber. Synthetic fiber is not recommended.
   ③ Please slowly peel off protective film, because static electricity may be charged.

4) If it is necessary to store LCD modules for a long time, please comply with the following procedures. If storage condition is not satisfactory, display (especially polarizer) may be deteriorated or soldering I/O terminals may become difficult (some oxide is generated at I/O terminals plating).

   ① Store as delivered by Optrex
   ② If you store as unpacked, put in anti-static bag, seal its opening and store where it is not subjected to direct sunshine nor fluorescent lamp.
   ③ Store at temperature 0 to +35℃ and at low humidity. Please refer to our specification sheets for storage temperature range and humidity condition.

5) The module does not contain excess current limiter.
   Please design the limiter to cut excess current in your power supply circuit.

6) Liquid crystal may be leaked when display is broken. Never taste it. If your hands or clothes touch it, please immediately wash using soap.

7) The connection between the bezel and V_{SS} (GND) is not specified in the module.
   (Some module do not maintain connection between them.)
   Please consult OPTREX to specify the connection.

Optrex shall not be responsible for any infringement of industrial property rights of third parties in any country arising out of the application or use of Optrex Products, except which directly concern the structure or production of such products.