EUROLITE LED STP-10 10x3W Bar

No. 42103487 ..... 3200K, 6°
No. 42103488 ..... 6500K, 6°
No. 42103489 ..... 3200K, 25°
No. 42103490 ..... 6500K, 25°

+ Equipped with 10 x 3 W LEDs
+ For use on stages, catwalks, crossbeam systems, or decoration
+ DMX-controlled operation or stand-alone operation with Master/Slave function
+ Each LED can be controlled individually

DMX

HIGH POWER LED







• 5 or 12 DMX channels selectable for numerous applications • Equipped with 10 x 3 W LEDs • For use on stages, catwalks, crossbeam systems, or decoration • DMX-controlled operation or stand-alone operation with Master/Slave function • Each LED can be controlled individually • 10 built-in programs can also be called up via DMX controller • Adjustable speed for internal programs, strobe effect and dimmer intensity via DMX • Strobe effect with 1-20 flashes per second • Sound-controlled via built-in microphone • Extreme and lightning-fast light displays • Elegant slim housing • Floor, ceiling or trussing installation possible • Delivered with power cord and safety-plug • Available in two color-temperatures • Addressing via control panel with 4-digit LED display • DMX control via every standard DMX controller • Feed-through output allows to power another device • After every 8 LED bars the fixtures must have a renewed connection with the power mains





Technical specifications:

Power supply:	*230 V AC, 50 Hz ~*
Power consumption:	*65 W*
Number of DMX channels:	*5/12*
DMX512 connection:	*3-pin XLR*
Flash-rate:	*20 Hz*
LED type:	*3 W, white*
Number of LEDs:	*10*
Dimensions (LxWxH):	*1070 x 90 x 145 mm*
Weight:	*3.5 kg*

EUROLITE LED ACS BAR-12 RGB 12x1W

No. 42109925

+ Equipped with 12 x 1 W LEDs (RGB)
+ Beam angle approximately 16°
+ Floor, ceiling or trussing installation possible
+ Static colors, RGB color blend, 6 internal programs, dimmer and strobe settings

NEW

DMX

HIGH POWER LED







• Operable in stand-alone mode or via DMX • DMX512 control possible via any commercial DMX controller (occupies max. 5 channels) • 3 or 5 DMX channels selectable for numerous applications • Sound-control via built-in microphone • Adjustable microphone sensitivity via control panel • Comfortable addressing and setting via control panel with LED screen and three operating buttons • Functions: Static colors, RGB color blend, 6 internal programs, dimmer and strobe settings via DMX, Master/Slave • Equipped with 12 x 1 W LEDs • Beam angle approximately 16° • Floor, ceiling or trussing installation possible • Locking possibility at the mounting bracket • Ready for connection via power cord with IEC plug for direct KLS-connection • For stand alone operation you need a normal power cord with safety plug



Technical specifications:

Power supply:	*230 V AC, 50 Hz ~*
Power consumption:	*20 W/40 VA*
Number of channels:	*3/5*
DMX-512 connection:	*3-pin XLR*
Sound-control:	*via built-in microphone*
LED-type:	*1 W*
Number of LEDs:	*12*
Beam angle:	*16°*
Dimensions (LxWxH):	*80 x 285 x 130 mm*
Weight:	*1.4 kg*

Accessories:

EUROLITE TH-50 Theatre hook, silver	*No. 58000650*
Safety bond A 3x600mm up to 5kg, silver	*No. 58010310*
IEC cable 0.6m 3x0.75	*No. 3023520L*

Delivery, technical changes, errors and omissions exempted. Please take notice of the user manuals and latest information which can be downloaded from our site. All pictures are similar and partially symbolic.