

DSP-26

Order No. 25.5780

Digital speaker management system

- 2 analogue inputs and 6 analogue outputs (XLR, balanced)
- 64-bit DSP, sampling rate: 96 kHz
- Dynamic range: > 114 dB
- Latency: < 1 ms
- Routing fader for user-defined routing of the inputs to the outputs
- Graphic user interface, PC editing software
- 50 user presets can be stored
- Remote control via USB
- Dot matrix display with 2 x 16 characters
- VU meter with 8 LEDs for each channel, level display and peak
- 482 mm (19") rack installation, 1 RS

Input (data for each channel):

- Gain control: -48 dB to +12 dB

Output (data for each channel):

- Gain control: -48 dB to +12 dB
- 10 parametric equalizers with 8 types of filters each
- 2 crossover networks with Butterworth, Linkwitz-Riley and Bessel filters as well as individually adjustable types of filters from 6 to 24 dB/oct.
- Delay to be switched between time (ms) and distance (m): 5 ms max. in steps of 10 µsec or 1.71 m max in steps of 3.4 mm
- Limiter, threshold: from -48 dBu to +9 dBu
- Mute
- Routing mix for level adjustment via routing fader
- Selectable phase (invert, 180°)

Model	DSP-26
Frequency range	10-30,000 Hz
Input signal	≤ 10 V
Output signal	≤ 2 V
Crossover frequency	70 Hz-1 kHz, 12 dB/oct., 910 Hz-8 kHz, 12 dB/oct., subwoofer 80/120 Hz, 24 dB/oct.
S/N ratio	> 110 dB
THD	< 0.005%
Power supply	via encl. plug-in power supply
Dimensions	482 x 44 x 175 mm, 1 RS
Weight	1.6 kg

