SPAN		Uniformly Distributed Load UDL		DEFLECTION		Centre Point Load CPL		DEFLECTION		Single Load Third Points Load per Point TPL		Single Load Fourth Points Load per Point QPL		Single Load Fifth Points Load per Point FPL		SPAN
m	ft	kg/m	lbs/ft	mm	inch	kgs	lbs	mm	inch	kgs	lbs	kgs	lbs	kgs	lbs	total weight
1	3.3	1985,3	1335.8	1	0.04	1985,3	4381.6	1	0.04	992,7	2190.8	660,9	1458.7	496,3	1095.4	5,1
2	6.6	990,1	666.2	4	0.16	1980,2	4370.3	3	0.12	990,1	2185.2	658,4	1453.0	495,1	1092.6	10,2
3	9.8	658,4	443.0	9	0.35	1405,1	3101.1	7	0.28	987,6	2179.5	655,8	1447.4	493,8	1089.8	15,3
4	13.1	492,5	331.4	17	0.67	1049,4	2316.0	13	0.51	787,0	1737.0	524,7	1158.0	435,5	961.1	20,4
5	16.4	334,0	224.7	26	1.02	834,9	1842.7	21	0.83	626,2	1382.0	417,5	921.3	346,5	764.7	25,5
6	19.7	230,4	155.0	37	1.46	691,1	1525.2	30	1.18	518,3	1143.9	345,5	762.6	286,8	633.0	30,6
7	23.0	167,9	113.0	51	2.01	587,6	1296.9	41	1.61	440,7	972.7	293,8	648.4	243,9	538.2	35,7
8	26.2	127,3	85.7	66	2.59	509,4	1124.2	53	2.08	382,0	843.2	254,7	562.1	211,4	466.6	40,8
9	29.5	99,6	67.0	84	3.31	448,0	988.7	67	2.63	336,0	741.5	224,0	494.3	185,9	410.3	45,9
10	32.8	79,7	53.6	103	4.06	398,3	879.1	83	3.27	298,8	659.3	199,2	439.6	165,3	364.8	51,0
11	36.1	65,0	43.7	125	4.92	357,3	788.5	100	3.94	267,9	591.3	178,6	394.2	148,3	327.2	56,1
12	39.4	53,8	36.2	149	5.87	322,6	712.0	119	4.69	241,9	534.0	161,3	356.0	133,9	295.5	61,2
13	42.6	45,1	30.3	175	6.89	292,9	646.4	140	5.51	219,7	484.8	146,4	323.2	121,5	268.2	66,3
14	45.9	38,1	25.7	202	7.95	267,0	589.4	162	6.38	200,3	442.0	133,5	294.7	110,8	244.6	71,4
15	49.2	32,6	21.9	233	9.17	244,3	539.2	186	7.32	183,2	404.4	122,2	269.6	101,4	223.8	76,5
16	52.5	28,0	18.8	264	10.39	224,1	494.6	212	8.35	168,1	370.9	112,0	247.3	93,0	205.3	81,6

1 inch = 25,4 mm | 1m = 3.28 ft | 1 lbs = 0,453 kg

- Loading figures only valid for static loads and spans with two supporting points
- Spans must be supported at each end
- If dynamic loads or wind loads are involved, or more supporting points are applied, contact a structural engineer or Prolyte Customer Service
- Loading figures are based on German DIN standards; to comply with BS 7905-2 / ANSI E1.2-2006

BAUART RWTÜV GEPRÜFT

Mark approval certificate No. 2258/04.
Test report No. 2257/04.
TUV certification only valid for loading table above.